

OROPRO 040

ACRYLIC PAINT

Matt acrylic paint, made with acrylic styrene emulsions, of great hardness, for the decoration of ceilings, walls, parking lots and all types of interior masonry in general. With mold preservative.

Physical features

Viscosity (Brookfield sp6 10rpm)	13000 – 18000 cpoise	
Specific weight	1,61 g/mL	
Solids	65%	
VOC	<30 g/L	Limit value (2010) according to directive 2004/42 / EC for this product (subcategory cat.a.a.): 30 g / L
Color	White	
Efficiency	8 – 10 m ² /L	(150 – 190 g/m ²)
Appearance in the can	Viscous liquid	
Appearance in dry film	Matt and smooth finish	
Fire classification	B-s1,d0	
Stability (without opening the can)	12 months at 10 – 25°C	
Gloss	<3%	

Product use

Support	Cement, concrete, plaster ... (do not apply on glue, temper or lime)
Support preparation	The surface must be dry, well set, without salt, sand or fissures. According to NTE-RPP-24.
Product preparation	Do not paint below 5°C, nor with rainy weather. Homogenize the product well before use.
Application system	Brush, Roller, Pneumatic gun, Airless gun
Dilution	Up to 20% with water (the first coat)
Application	1 first coat diluted to 20% with water for a good penetration, and 2 more coats of undiluted finish at 50 - 60 µm dry film thickness.
Drying/curing	Dry touch: 30 minutes Drying time is very influenced by the applied quantity, the environment and the substrate's type and condition.
Repaint	4 – 6 hours
Cleaning	WATER

Recommended system

Recommended system	Primer	Topcoat
Plaster, concrete	OROPRO 040	OROPRO 040

Additional information

Security	Consult package labeling. For more information request the Safety Sheet.
Storage time	1 year

Instructions included in this technical data sheet and its advices have been got from our own experiences and they should be taken as guidelines, with no commitment from us. Values shown in this technical data sheet are only a reference and must not be considered as strict. The customer can and should check the goods provided by us, verifying they are right and valid for their offered purposes. It is completely out of our control the correct application of the product as well as its adequate use, variable working circumstances, etc, so this means the customer is responsible for them. This stated, we completely guarantee the quality of our products, as a consequence of our sales and delivery commitments previously established.

Product	Product code	Brand	Author	Date	Version	Replaces	Page	Language
OROPRO 40	00R040XXXZZZ	OROPAL	IRURENA GROUP	03.01.24	1	Any previous version	1/2	EN