



# OROPRO 080

## ACRYLIC PAINT

Washable matt emulsion paint for high-quality decoration, based on vinyl acrylic copolymers, suitable for interior and exterior decoration of residential properties, hotels, etc., providing a super fine matt finish with excellent coverage. Contains biocides, providing fungicidal and anti-mould protection to the paint. Applies easily.

### Physical parameters

Viscosity (Brookfield sp6 10rpm)	20000 – 30000 cpoise
Specific gravity	1,57 g/mL
Sólids content	64%
VOC	<2 g/L The limit value (2010) Directive 2004/42/EC for this product (sub. cat. A/a): 30g/L
Colour	White
Spreading rate	7 – 9 m <sup>2</sup> /L (180 – 220 g/m <sup>2</sup> )
In-can appearance	Viscous liquid
Dry film appearance	Matte, covering and washable finish
Fire classification	B-s1,d0
Stability (unopened container)	12 months at 10 – 25°C
Gloss	3%
Washability	Class 1 (UNE 13.300)

### Product use information

Surface	Cement, concrete, plaster... (do not apply over glue, distemper or lime)
Surface preparation	The surface must be dry, well-cured, without stains, saltpetre, sand, or cracks. According to NTE-RPP-24.
Product preparation	Do not paint below 7°C or during rainy weather. Thoroughly homogenize the product before use.
Application method	Brush, Roller, Pneumatic Spray Gun
Dilution	Up to 10% with water (for the first coat)
Aplicación	1 first coat diluted by 10% with water for good penetration, and 2 more finishing coats undiluted at 50 - 60 µm.
Drying	Touch dry: 30 minutes <small>Drying time is greatly influenced by the grammage, type and condition of the substrate and environmental conditions.</small>
Overcoat	4 – 6 hours
Cleaning	WATER

### Application process

	Primer	Top Coat
Plaster, Concrete	OROPRO 080	OROPRO 080

### Additional information

Safety	Check the labeling on the container. For more information, request the Safety Data Sheet.
Storage time	1 year

Instructions included in this technical data sheet and its advices have been got from our own experiences and they should be taken as guidelines, with no commitment from us. Values shown in this technical data sheet are only a reference and must not be considered as strict. The customer can and should check the goods provided by us, verifying they are right and valid for their offered purposes. It is completely out of our control the correct application of the product as well as its adequate use, variable working circumstances, etc, so this means the customer is responsible for them. This stated, we completely guarantee the quality of our products, as a consequence of our sales and delivery commitments previously established.

Producto	Código artículo.	Marca	Autor	Fecha	Versión	Reemplaza	Página	Idioma
OROPRO 080	00R080XXXZZ	OROPAL	IRURENA GROUP	31.01.24	1	Any previous version	1/1	EN