

OROSPORT 303

SWIMMING POOL PAINT

Acrylic matte water paint, designed exclusively for pool painting. Among other characteristics, it stands out its fast drying, good repaintability without sanding and excellent resistance to aging due to the action of ultraviolet rays.

Physical parameters

Viscosity (Brookfield sp6 10rpm)	13000 – 20000 cpoise
Specific gravity	1,45 – 1,50 g/mL
Sólids content	61%
Colour	Blue caribbean sea
Spreading rate	7 – 9 m ² /L (165 – 200 g/m ²)
In-can appearance	Viscous liquid
Dry film appearance	Matt topcoat with good covering and leveling
Stability	12 months at 10 – 25°C
Gloss	<5%
Adhesion	100% (Máx: GT0)
Washability	>5000 doble cleaning

Product use information

Surface	Cement, concrete
Surface preparation	Brush cement surfaces with 10% diluted hydrochloric acid in water, using gloves for this. Wash with clean water and dry. If you are going to apply on old paints, scrape thoroughly and wash with a detergent. Subsequently, rinse and dry.
Product preparation	Do not paint below 7°C. Before applying, homogenize the product well with a spatula
Application method	Brush, Roller, Airless Gun, Airless
Thinning	Up to 15% with water (the first hand)
Aplicación	1 hand with a brush diluted 15% with water, let harden, and 1 or 2 more undiluted hands at 50 - 60 µm dry. Once applied, allow to harden a week before filling the pool
Drying	Touch drying time: 1 hour Drying time is very influenced by the dry film weight, type and state of the substrate and weather conditions...
Overcoat	6 – 12 hours
Cleaning	WATER

Application process

Application process	Primer/Intermediate	Top coat
Concrete, Cement	OROSPORT 303	OROSPORT 303

Additional information

Safety	Consult package labelling. For further information, ask for the Material Safety Data Sheet
Storage	1 year

Instructions included in this technical data sheet and its advices have been got from our own experiences and they should be taken as guidelines, with no commitment from us. Values shown in this technical data sheet are only a reference and must not be considered as strict. The customer can and should check the goods provided by us, verifying they are right and valid for their offered purposes. It is completely out of our control the correct application of the product as well as its adequate use, variable working circumstances, etc, so this means the customer is responsible for them. This stated, we completely guarantee the quality of our products, as a consequence of our sales and delivery commitments previously established.

Product	Product code	Brand	Author	Date	Version	Replaces	Page	Language
OROSPORT 303	03R303163ZZZ	OROPAL	IRURENA GROUP	03.01.17	1	Any previous version	1/1	EN