

OROSPORT 307

SPORT CENTER FLOORING PAINT

Acrylic matte water paint, designed exclusively for pool painting. Among other characteristics, it stands out its fast drying, good repaintability without sanding and excellent resistance to aging due to the action of ultraviolet rays.

Physical parameters

Viscosity (Brookfield sp6 10rpm)	5000 – 10000 cpoise depending the colour
Specific gravity	1,25 – 1,40 g/mL depending the colour
Sólids content	45 - 60% depending the colour
Colour	White, Green tennis, Grey, Red oxide
Spreading rate	6 – 9 m ² /L (170 – 220 g/m ²)
In-can appearance	Viscous liquid
Dry film appearance	Matt topcoat with good resistance
Stability	12 months at 10 – 25°C
Gloss	<4%
Adhesion	100% (Máx: GT0)
Washability	>5000 doble cleaning

Product use information

Surface	Cement, concrete, asphalt
Surface preparation	The cement surfaces must be dry, without sands or dust. The surfaces of asphalt will be agglomerate with gravel, porous, without dust and dry. Do not apply the product over solvent base paints.
Product preparation	Do not paint below 7°C. Before applying, homogenize the product well with a spatula
Application method	Brush, Roller, Airless Gun, Airless
Thinning	Up to 10% with water (the first hand)
Aplicación	1 hand with a brush diluted 10% with water, let harden, and 2 undiluted hands at 50 - 60 µm dry. Once applied, allow to harden a week before filling the pool
Drying	Touch drying time: 1 hour Drying time is very influenced by dry film weight,, type of the substrate and weather conditions..
Overcoat	6 – 12 hours
Cleaning	WATER

Application process

Application process	Primer/Intermediate	Top coat
Concrete, Cement, Asphalt	OROSPORT 307	OROSPORT 307

Additional information

Safety	Consult package labelling. For further information, ask for the Material Safety Data Sheet
Storage	1 year

Instructions included in this technical data sheet and its advices have been got from our own experiences and they should be taken as guidelines, with no commitment from us. Values shown in this technical data sheet are only a reference and must not be considered as strict. The customer can and should check the goods provided by us, verifying they are right and valid for their offered purposes. It is completely out of our control the correct application of the product as well as its adequate use, variable working circumstances, etc, so this means the customer is responsible for them. This stated, we completely guarantee the quality of our products, as a consequence of our sales and delivery commitments previously established.

Product	Product code	Brand	Author	Date	Version	Replaces	Page	Language
OROSPORT 307	03R307XXXZZZ	OROPAL	IRURENA GROUP	03.01.17	1	Any previous version	1/1	EN