




\* Maximum durability observed.

## IRUXIL BIO Lasur

**RENEWABLE  
ORIGIN  
PRODUCT**

Content greater than 80%  
in Renewable Sources



### PRODUCT DESCRIPTION

Coloured topcoat of renewable origin with specially selected iron oxides. Its purpose is to protect and beautify any type of wood, whether indoors or outdoors.

Enhances the natural beauty of wood, colouring it and protecting it against graying.

It is certified with the Ecolabel seal for exterior varnishes.

### GENERAL PROPERTIES

**Content > 80% in renewable sources.**

Very easy application by brush, short-haired roller and / or airbrush projection.

Effective protection against atmospheric elements (bad weather).

Great elasticity and adherence to wood (does not crack).

Great colour stability. Contains UV absorbers that protect wood from sunlight (photodegradation).

Quick drying even on tropical woods.

Absence of odors during application.

Not flammable.



## CHARACTERISTICS

Ford Cup No. 4 Viscosity	90"
Specific weight	1,04 g/cm <sup>3</sup> .
Appearance on the container	Fluid liquid.
Dry film appearance	Color according to sample
Stability unopened (protect from frost)	12 months.
Performance	10-13 m <sup>2</sup> /l (per coat)
Drying times (100 g/m <sup>2</sup> at 20°C and 60% R.H.)	1-2 h to recoat between coats.

## APPLICATION

**Support and preparation:** Applicable on all types of wood. However, in outdoor applications the use of woods of doubtful durability should be avoided. The wood must be clean of dust and dirt and free of any layer of varnish or paint, in order to facilitate good penetration and adherence of the product to the substrate. Do not apply on wood that contains more than 15% moisture.

**Application:** The product is ready for use. Shake to ensure colour uniformity. Apply 3 coats of 80-100 gr/m<sup>2</sup>. For a better finish, apply in the direction of the wood grain. Sand gently between coats at 1-2 hours intervals, avoiding application in cold and humid environments. If necessary, dilute with water.

**Maintenance:** If over time signs of degradation are observed, just gently sand the surface in question and apply 1-2 coats of **IRUXIL BIO**.

**Cleaning:** Use water. Do not pour waste down the drain.

## PRESENTATION:



**OBSERVATIONS:** The colourless version offers less protection against solar radiation outdoors than the rest of the colours in the range, so it is recommended for use indoors or for periodic maintenance of exterior carpentry.