




INTERIOR PARQUET – SUELO DE MADERA



PRODUCT DESCRIPTION

Single component water-based varnish, based on polyurethane resins, specifically designed for varnishing wooden floors and parquet. Non-flammable and virtually odourless. Shine grades: matte, satin, and gloss.

GENERAL PROPERTIES

- Easy application with a brush and short-haired roller.
- Excellent resistance to abrasion.
- Outstanding chemical resistance to household products.
- Good resistance to rubbing and scratching.
- Low odor during application.
- Allows cleaning of working tools with water.



CHARACTERISTICS

Ford Cup N°4 (PE-09) Viscosity	23".
Mixture solids (PE-05):	28%.
pH (PE-23):	7,8
Abrasion resistance Taber (PE-28, wear after 25 c.):	10-15 mg.
Appearance on the container	Fluid liquid with a milky appearance.
Appearance of the dry film	Clear.
Stability when unopened (protect from freezing)	12 months.

APPLICATION

Support and preparation: Wood previously roughened with 30-36 grit sandpaper and refined with 60 and 80 grits. Remove sanding residue by blowing or using a cloth. We recommend using wood types with proven results. Introducing new wood types to the market will require prior testing to validate them for the intended purposes.

Application: The product is ready for use. Shake well to ensure product uniformity. Apply 2-3 coats of 60-80 g/m², sanding between layers with fine-grit sandpaper (240-280). To aid drying, avoid application in cold and humid environments. Maintain the product at 20-25°C. If dilution is necessary, use water (preferably demineralized).

Drying times:

Drying	1-2h
Sanding and Repainting	3-6h

**The drying time is heavily influenced by the weight, the type of support, and the environmental conditions during drying.*

It is recommended to provide some ventilation in the application area to aid water evaporation, prevent oversaturation, and promote drying. After applying the final coat, allow at least 48 hours to achieve optimal scratch resistance.

Cleaning: Use water. Do not pour residues down the drain. If the material has dried, Acetone will be used for cleaning.

PRESENTATION:



490 CLEAR

FINISH
GLOSSY
SATIN
MAT

OBSERVATIONS: PARQUET-SUELOS de MADERA It combines the advantages of water-based varnishing (low odor, minimal solvent content, etc.) with excellent chemical and mechanical performance (abrasion, rubbing, and scratching). It's recommended to apply the final coat after one night of drying.