



ACEITE DE TEKA



PRODUCT DESCRIPTION

ACEITE DE TEKA (teak oil) is a revitalizer for any type of wood. Help to enhance the natural tones of the wood. Protects and beautifies any type of timber, either indoors or in outdoor conditions. Formulated with natural oils.

GENERAL PROPERTIES

- Easy to use.
- Great wetting power.
- Warm and silky finish. Respects the natural look of the wood.
- Wood protector that repels the water.
- Non film forming.
- Easy maintenance. It restores the oils that the wood lost over time.
- Doesn't slip.



CHARACTERISTICS

Viscosity Copa Ford N°4	12"
Specific weight	0.840 g/cm ³ .
Appearance in the container	Liquid.
Dry film appearance	Color (variable upon ref).
Stability (closed can)	12 months.
Spreading rate	15 m ² /l aprox
Drying time (60 g/m ² at 20°C):	8h between coats. 24 hours full dry

APPLICATION

Support and preparation: All type of woods, for outdoor select durable wood species. The humidity will be below 15%. Clean and remove old paintings or varnishes remains of the wood with the aim of make an easier infiltration to the oils.

Application: ACEITE de TEKA is ready to use. Shake the product before use. To facilitate the application and wetting of wood, avoid the application on the wood exposed to direct sun or reheated. Apply until saturate by a brush or roller uniformly. Leave for 20-30 minutes. Clean the excess with a cloth. For a perfect finish once the first coat dries, spread out a second coat with a cloth. In some tropical timber (ipe, merbau, iroko, etc.) may need more drying time.

Maintenance: Its maintenance is simple as it does not create a film. Just clean the wood and apply again ACEITE de TEKA.

Cleaning: Use White spirit or turpentine.

Risk for spontaneous combustion of clothes used for application. The oxidation of the oil generates heat enough to self-ignition of the oil-wetted clothes. To avoid the risk of self-combustion of cloths and used tools, we recommend to moisture them with water and remove them in a sealed plastic bag or leave them dry outdoor in extended way.

PRESENTATION: Available in different shades:



490 CLEAR



499 HONEY



420 TEAK

OBSERVATIONS:

Solvent-base product. Observe the safety data sheet during the process. In outdoor application the colored shades, HONEY (honey) or TEAK, have an extra protection against sun UV radiation.