



TINTES AL AGUA [WATER-BASED DYES]



PRODUCT DESCRIPTION

Range of liquid dyes for general use, specially designed for wood staining in the Furniture Industry and accessories (parquet and floorboards). This range is particularly compatible with water. The application method, the substrate (veneer or solid wood), and the desired effect are factors to consider.

GENERAL FEATURES

- Application with spray gun (airbrush), roller, brush, immersion, or with a cloth.
- Fully compatible with water and alcohols.
- High transparency and pure tone.
- Excellent coloring power.
- Good light resistance.
- Moderate bleeding effect when overcoating with water-based primers.
- No odors during application.
- Non-flammable.

CHARACTERISTICS

IRURENA GROUP Ctra. De Tolosa s/nº. Apdo. 30 20730 Azpeitia - Gipuzkoa - Spain

Review: 1/03-2021

The information contained in the data sheet and the subsequent advice from it derives, are a consequence of our knowledge, do and how to proceed and must be understood as guidelines to follow, without commitment on our part. The values shown in this data sheet are key data and should not be regarded as a specification. The client can and must examine the goods supplied by us, verifying their qualifications and ability to obtain ends pursued. A correct application, proper use, changes in working conditions, etc., remain outside of our control, whichever therefore hold the customer. From all the review, is understood to fully guarantee the quality of our products because of the sale and supply commitments previously acquired.



Cup Ford N°4 Viscosity	10"
Specific weight	1,000 g/cm ³ (depending on the tone).
Appearance in the container	Fluid liquid.
Dry film appearance	Colour s/m.
Stability without opening the container (protect from frosts)	12 months.
Performance	15-20 m ² /l (1x40-60 g/m ²)
Drying times (50 g/m ² a 20°C and 60% de H.R)	1 h.

APPLICATION

Support and preparation: Sand the wood with suitable grit sandpaper, refining with 150-180 grit sandpaper. Remove sanding residue. Do not apply on woods containing more than 15% moisture.

Application: The product is ready for use. Shake well to ensure colour uniformity. Apply a coat of 20-50 g/m². For a more uniform staining, apply following the wood grain. Avoid application in cold and humid environments. If necessary, dilute with water.

Tools cleaning: Use water. Do not pour residues down the drain.

PRESENTATION:

